

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (currently amended) A Seal seal for an optical unit constituting an automobile indicator or illuminating light, intended to be mounted between ~~this~~ the optical unit and a support in which it is inserted, the seal ~~consisting of~~ comprising  
  
a sheet of flexible material provided with an internal orifice intended to receive the unit, wherein the sheet of flexible material comprises ~~it consists of~~ at least one material with a self-adhesive surface skin formed by extrusion; and  
  
~~, the seal comprising, on at least one of its edges,~~ at least one lip with a height greater than the thickness of the sheet of flexible material and perpendicular thereto, wherein said at least one lip is located on at least one edge of said seal.
2. (currently amended) The Seal seal according to claim 1, which consists of various coextruded materials with different hardnesses.
3. (currently amended) The Seal seal according to claim 1, which consists at least partially of cellular EPDM.
4. (withdrawn) Method of manufacturing a seal according to claim 1, which method consists of producing a strip by extrusion, cutting it into sheets with a dimension equal to that of the seal and cutting out the said internal orifice.

5. (withdrawn) Method according to Claim 4, wherein the cutting into sheets and the cutting of the said orifice are simultaneous.
6. (new) A seal for an optical unit constituting an automobile indicator or illuminating light, intended to be mounted between the optical unit and a support in which it is inserted, the seal comprising
  - a sheet of flexible material provided with an internal orifice intended to receive the unit, wherein the sheet of flexible material comprises at least one material with a self-adhesive surface skin formed by extrusion; and
  - at least two lips with a height greater than the thickness of the sheet of flexible material and perpendicular thereto, wherein said at least two lips are located along at least one edge of said seal.
7. (new) A seal for an optical unit constituting an automobile indicator or illuminating light, intended to be mounted between the optical unit and a support in which it is inserted, the seal comprising
  - a sheet of flexible material provided with an internal orifice intended to receive the unit, wherein the sheet of flexible material comprises at least one material with a self-adhesive surface skin formed by extrusion; and
  - a lip with a height greater than the thickness of the sheet of flexible material and perpendicular thereto, wherein a junction between said lip and said sheet of flexible material is substantially perpendicular to the plane of the seal, and

wherein said lip comprises a material of a different hardness than that of said sheet of flexible material.

8. (new) A seal for an optical unit constituting an automobile indicator or illuminating light, intended to be mounted between the optical unit and a support in which it is inserted, the seal comprising

a sheet of flexible material provided with an internal orifice intended to receive the unit, wherein the sheet of flexible material comprises at least one material with a self-adhesive surface skin formed by extrusion; and

a lip with a height greater than the thickness of the sheet of flexible material and perpendicular thereto, wherein said lip is located along only a portion of a perimeter of said sheet of flexible material.